

DCS125(6)-3X-5449 P/N 94047

BEHLMAN's DCS Series of COTS power supplies are low cost, highly reliable, switch-mode units built for high-end industrial or MIL applications. DCS Series power supplies are available in power ranges from 100 up to 2000 Watts. DCS power supplies can be factory re-configured to accept a wide variety of inputs (AC or DC) and can be factory re-configured to supply a variety of single or multiple DC outputs. These rugged power supplies are built to support the rigors of airborne, shipboard & mobile applications and are designed to meet the input power requirements of MIL-STD-704. Units are Base-Plate cooled. The standard DCS has been re-configured to meet the stated criteria.

INPUT(3X): Input Transient protection: Per Mil-STD-704, 50 ms Hold-Up Time @ 125W out.
28 VDC (18 – 36 VDC Range)

OUTPUT(s):

(6) Six				Min.*	Max.*	Ripple RMS
1	+15VDC	@	0.84A	+14.85	+15.15	25mv.
2	-15VDC	@	0.83A	-14.25	-15.75	25mv.
3	+12VDC	@	4.0A	+11.88	+12.12	25mv.
4	-12VDC	@	3.0A	-11.50	-12.50	25mv.
5	+5.1VDC	@	15A	+5.00	+5.20	25mv.
6	-5.1VDC	@	5.0A	-5.00	-5.20	25mv.

* Combined Load Regulation & Line Regulation (minimum to full-load)

Current Limit: Short Circuit and Over-Current protected.
Over Voltage: 120% (Typical).
Efficiency: 85% (Typical).
Hold Up: 50 msec for all outputs @ 125W out max.

GENERAL CHARACTERISTICS: see O&C drawing 24075

Isolation:
Input to Output: 1000 VDC
Input to Case: 1000 VDC
Output to Case: 200 VDC
Dimensional Data: 6.0"L X 3.5"W X 1.5"H
Weight: 2.4 lbs
J1- Input M83513/10-A01NP
J2 – Output M83513/13-D01NP
Mounting: See DWG 24075 for Outline and Connections

ENVIRONMENTAL:

Operating Temperature: -40° C to +85° C @ Base-Plate
Storage Temperature: -45.5° C to +100° C
Designed to meet the following Standards:
Shock: MIL-S-901; MIL-STD-810
Vibration: MIL-STD-167; MIL-STD-810; RTCA/DO-160
Humidity: MIL-STD-810
EMI/EMC: MIL-STD-461C/D; RE102 with proper shielding.



Headquarters:
80 Cabot Court Hauppauge, NY 11788
(631) 435-0410 (800) 874-6727 Fax: (631) 951-4341

Behlman
e-mail: sales@behlman.com
Web-site: www.behlman.com

West Coast Office:
2363 Teller Road Suite 108 Newbury Park, CA 91320
(805) 375-7046 (800) 456-2006 Fax: (805) 498-2147