

# BEHLMAN

## DCS750( ) - (Input) - (V, A)

Behlman's DCS750 series of COTS power supplies are low cost, highly reliable, switch mode units built for high-end industrial or MIL applications. The DCS750 can accept a wide range of inputs and can supply a variety of DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Units are Base Plate cooled.

<b>INPUT ( I )</b>	Input Transient protection: Per Mil-STD-704
-1:	85-265 VAC, 47-440 Hz, Power Factor Corrected
-2:	90-132 or 180-264 VAC, 47-440 Hz, Auto-ranging
-3:	20-32 VDC
-4:	36-72 VDC
-5:	200-400 VDC
-6:	115/200 VAC, 3 phase, 47-440 Hz



<b>OUTPUT(S):</b>	<b>S ( Single); D (Dual); T (Triple); Q (Quad)</b>
Voltage: ( V )	2 to 48 VDC +/-1%
Current: ( A )	( X ) Amps. Maximum power 750 watts
Load Regulation:	0.2% Maximum (0-100%)
Line Regulation:	0.2% Maximum
PARD-Ripple & Noise:	1% Typical
Current Limit:	Short circuit and over-current protected
Over voltage:	Included
Efficiency:	72% to 85% depending on model
Remote Sense:	0.6V compliance

### GENERAL CHARACTERISTICS

Isolation	
Input to Output:	1000 VDC minimum
Input to Case:	1000 VDC minimum
Output to Case:	200 VDC minimum
Dimensional Data:	8.75"L X 5.0"W X 2.0"H
Weight:	3.0 lbs
J1- Input:	D Type connector
J2- Output:	D Type connector

### ENVIRONMENTAL: Designed to meet the following MIL Standards

Operating Temperature:	-40 to +85 degrees C Base Plate
Storage Temperature:	-40 to + 100 degrees C
Shock:	MIL-S-901; MIL-STD-810
Vibration:	MIL-STD-167; MIL-STD-810; RTCA/DO-160
Humidity:	MIL-STD-810
EMI/EMC:	MIL-STD-461C/D; RTCA/DO-160D. RE102 with proper shielding.

Proudly made  
  
in the U.S.A.

#### Headquarters

80 Cabot Court, Hauppauge, NY 11788  
(631) 435-0410 (800) 874-6727 Fax (631)951-4341

**BEHLMAN**

e-mail: [sales@behlman.com](mailto:sales@behlman.com)  
Web-site: [www.behlman.com](http://www.behlman.com)

#### West Coast Office

2363 Teller Road Suite 108, Newbury Park, CA 91320  
(805) 375-7046 (800) 456-2006 Fax (805) 498-2147